# MAXIGEAR EP-X 85W-90 LS

# High Quality Limited Slip Automotive Gear Oil

## **Description**

Automotive gear oil with limited slip quality, produced by using high quality advanced base oils and a balanced and advanced additives package.

### **Applications**

Can be used in passenger car, heavy duty vehicle and off-road vehicle gear boxes and locked differentials requiring limited slip quality.

#### **Benefits**

- The limited slip feature provides perfect lubrication in all locked gear boxes requiring this quality, and working at high temperatures and heavy loads.
- Prevents noise in locked differentials.
- Provides a high level of protection for all differentials and gear boxes with GL-5 performance level.
- Facilitates starting at low temperatures, and prevents wear.
- Extends the oil change intervals.
- Provides excellent protection at high temperatures to ocur in transmissions continuously operating under limited slip conditions.

#### **Performance**

API GL-5. ZF TE-ML 05C-12C-21C

#### Typical Specifications\*

SAE Viscosity Grade		85W-90
Density, @ 15 °C, kg/m³	ASTM D-4052	0,900
Flash Point, COC, °C	ASTM D-92	220
Viscosity, 40 °C, mm²/s	ASTM D-445	160
Viscosity, 100 °C, mm²/s		15,5
Viscosity Index	ASTM D-2270	100
Pour Point, °C	ASTM D- 97	-24

<sup>\*</sup> Values shown may differ between productions.

