

MAXIMA 10W-40^{plus}

Synthetic Motor Oil with Improved New Formulation

Description

Maxima 10W-40 PLUS is a synthetic engine oil with up to 4 times wear protection by virtue of the improved new formulation. It is produced from synthetic base oils and new generation additive packages.

Applications

Suitable for all gasoline and diesel engines in the passenger cars and light commercial vehicles demanding SAE 10W-40 viscosity grade and ACEA A3/B4 engine oil performance level.

Benefits

- Provides maximum fuel economy.
- Keeps engine clean.
- Extends oil change interval.
- Provides best fuel efficiency and increases engine efficiency.
- Contributes to engine life by reducing friction.
- Quick start up at cold weather condition and fast engine wear protection.
- Ensures oil film thickness and provides protection against heavy driving conditions via stable viscosity.

Performance

API SL/CF, ACEA A3/B4, VW 501.01/505.00, MB 229.1

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, @ 15 °C, kg/m³	ASTM D-4052	0,870
Flash Point, COC, °C	ASTM D-92	234
Viscosity, 40 °C, mm²/s	ASTM D 445	86,5
Viscosity, 100 °C, mm²/s		13
Viscosity Index	ASTM D-2270	151
Pour Point, °C	ASTM D- 97	-30

^{*} Values shown may differ between productions.

